



QC4LD0561 series

Ultra-compact light source for plug-and-play

Preliminary

C00302-04 September 2026



1. DESCRIPTION

QC4LD0561 series, Lantana™ with fiber pigtail, is an ultra-compact light source with integrated driver and is a plug-and-play unit via USB communication.

2. FEATURES

- Compact plug and play driver-integrated unit.
- Patented high stability single frequency laser combining DFB laser and second harmonic generation.
- Unprecedented compact unit 38 x 62 x t22.7 mm (53 cc).
- CW/Modulation light source controlled via serial communication.

3. APPLICATION

- Flow Cytometry
- Cell Sorting
- Laser Microscopy
- Raman Spectroscopy


4. SPECIFICATIONS

(Ambient temp. = 25°C)			
Model Number	QC4LD0561-32xx	QC4LD0561-61xx	QC4LD0561-94xx
Peak Wavelength	532 +/- 1 nm	561 +/- 1 nm	594 +/- 1 nm
Output Power	xx = 10 : 10 mW xx = 15 : 15 mW xx = 25 : 25 mW	xx = 10 : 10 mW xx = 15 : 15 mW xx = 25 : 25 mW	xx = 02 : 2 mW
Maximum Output Power	xx = 10 : 13 mW xx = 15 : 20 mW xx = 25 : 30 mW	xx = 10 : 13 mW xx = 15 : 20 mW xx = 25 : 30 mW	xx = 02 : 3 mW
Power Stability	< 2% (under CW mode, 8 hrs)		
RMS Noise	< 1% at 120 kHz to 10 MHz (under CW mode)		
Polarization Ratio	> 12 dB		
Polarization Direction	In PMFs, the polarization is maintained along the slow axis.		
Digital Modulation Bandwidth	0 – 50 kHz		
Rise Time / Fall Time	< 5 μsec / < 3 μsec		


Model Number	QC4LD0561-32xx	QC4LD0561-61xx	QC4LD0561-94xx
Dimension	38 x 62 x t22.7 mm		
Weight	165 g		
External Clock & Sync Out Voltage	3.3V CMOS level		
Serial Communication	Lantana side : USB Type-C, PC side : USB Type-A		
AC Power Adapter	AC input voltage : 100~240 V - DC output voltage : 12 V		
Ambient Temperature	15 – 37°C		
Ambient Humidity	< 65%RH		
Power Consumption	2.2 W at 50 mW (Typ.)		

5. PRODUCT PART NUMBER

QC4LD0561- [] [] [] - [] []




6. OUTLINE DRAWING



7. SETUP

- Be sure to fix Lantana™ to heatsink before operation.
- Do not apply thermal grease between the heatsink and Lantana™.
- The mounting surface should be flat, within < 0.02 mm.
- Fixing screw size is 4-M2x8 or 4-#2x5/16.
- Lantana will overheat and shut down if it is not adequately heatsinked.
- The figure below shows the needed thermal impedance of heatsink.



8. NOTICE

- Safety Information

This product is classified as Class 3B laser product.

Please do not take a look at laser lighting in operations since laser devices may cause troubles to human eyes.

Please do not eat, burn, break and make chemical process of the products since they contain GaAs material.

- Handling products


Semiconductor lasers are easily damaged by external stress such as excess temperature and ESD.

Please pay attention to handling products, and use within range of maximum ratings.

QD Laser takes no responsibility for any failure or unusual operation resulting from improper handling, or unusual physical or electrical stress.

- RoHS

This product conforms to RoHS compliance related Directive (EU) 2015/863.



QD Laser, Inc.

Contact : info@qdlaser.com <https://www.qdl-laser.com/en>

Copyright 2026 All Rights Reserved by QD Laser, Inc.

206-1 Kamikurata-cho, Totsuka-ku, Yokohama, Kanagawa 244-0816, Japan

All company or product names mentioned herein are trademarks or registered trademarks of their respective owners. Information provided in this data sheet is accurate at time of publication and is subject to change without advance notice.